



103/112Gb/s QSFP28 LR4 Transceiver

APQP2LRB3CDL10

■ Product Features

- ✓ 4 LAN-WDM lanes MUX/DEMUX design
- ✓ 4 independent full-duplex channels up To 28Gbps data rate per wavelength
- ✓ Hot-pluggable QSFP28 footprint
- ✓ RoHS compliant and Lead Free
- ✓ Up to 10Km link length
- ✓ Power dissipation <4.5W (0~70°C)
- ✓ Commercial operating temperature optional



■ Applications

- ✓ 100GBASE-LR4
- ✓ 100GEthernet
- ✓ OTU4 4I1-9D1F

■ Product Selection

Part Number	Operating Case temperature	DDMI
APQP2LRB3CDL10	Commercial (0~70°C)	Yes



■ **Regulatory Compliance**

- ESD to the Electrical PINs: compatible with MIL-STD-883 Method 3015
- ESD to the Duplex LC Receptacle: compatible with IEC 61000-4-2
- Immunity compatible with IEC 61000-4-3
- EMI compatible with FCC Part 15 Class B EN55022 Class B (CISPR 22B) VCCI Class B
- Laser Eye Safety compatible with FDA 21CFR 1040.10 and 1040.11 EN60950, EN (IEC) 60825-1,2
- RoHS compliant with RoHS 2 (2011/65/EU)

■ **Pin Descriptions**

Pin	Symbol	Name/Description	Ref.
1	GND	Ground	
2	Tx2n	Transmitter Inverted Data Input, CML-I	
3	Tx2p	Transmitter Non-Inverted Data output, CML-I	
4	GND	Ground	
5	Tx4n	Transmitter Inverted Data Input, CML-I	
6	Tx4p	Transmitter Non-Inverted Data output, CML-I	
7	GND	GND	
8	ModSelL	The ModSelL is an input pin. When held low by the host, the module responds to 2-wire serial communication commands. The ModSelL allows the use of multiple QSFP+ modules on a single 2-wire interface bus. When the ModSelL is “High”, the module shall not respond to or acknowledge any 2-wire interface communication from the host. ModSelL signal input node must be biased to the “High” state in the module	
9	ResetL	The ResetL pin must be pulled to Vcc in the QSFP+ module. A low level on the ResetL pin for longer than the minimum pulse length (t_Reset_init) initiates a complete module reset, returning all user module settings to their default state. Module Reset Assert Time (t_init) starts on the rising edge after the low level on the ResetL pin is released.	
10	VccRx	+ 3.3V Power Supply Receiver	
11	SCL	2-Wire Serial Interface Clock	
12	SDA	2-Wire Serial Interface Data	



APQP2LRB3CDL10

13	GND	GND	
14	Rx3p	Receiver Non-Inverted Data Output, CML-O	
15	Rx3n	Receiver Inverted Data Output, CML-O	
16	GND	GND	
17	Rx1p	Receiver Non-Inverted Data Output, CML-O	
18	Rx1n	Receiver Inverted Data Output, CML-O	
19	GND	Ground	
20	GND	Ground	
21	Rx2n	Receiver Inverted Data Output, CML-O	
22	Rx2p	Receiver Non-Inverted Data Output, CML-O	
23	GND	Ground	
24	Rx4n	Receiver Inverted Data Output, CML-O	
25	Rx4p	Receiver Non-Inverted Data Output, CML-O	
26	GND	Ground	
27	ModPrsL	Module Present, connect to GND	
28	IntL	The IntL pin is an open collector output and must be pulled to host supply voltage on the host board. The INTL pin is de-asserted "High" after completion of reset, when byte 2 bit 0 (Data Not Ready) is read with a value of '0' and the flag field is read.	
29	VccTx	+3.3 V Power Supply transmitter	
30	Vcc1	+3.3 V Power Supply	
31	LPMODE	The LPMODE pin shall be pulled up to Vcc in the QSFP+ module. This function is affected by the LPMODE pin and the combination of the Power_over-ride and Power_set software control bits (Address A0h, byte 93 bits 0,1).	
32	GND	Ground	
33	Tx3p	Transmitter Non-Inverted Data Input, CML-I	
34	Tx3n	Transmitter Inverted Data Output, CML-I	
35	GND	Ground	
36	Tx1p	Transmitter Non-Inverted Data Input, CML-I	
37	Tx1n	Transmitter Inverted Data Output, CML-I	
38	GND	Ground	




Top Side
Viewed from Top

Bottom Side
Viewed from Bottom

Pin-out of Connector Block on Host Board

Recommend Circuit Schematic





Absolute Maximum Ratings

Parameter	Symbol	Min	Typ	Max	Unit	Ref.
Maximum Supply Voltage	Vcc	-0.5		+4.0	V	
Storage Temperature	TS	-40		+85	°C	
Operating Humidity	RH	0		85	%	

Recommended Operating Conditions

Parameter	Symbol	Min	Typ	Max	Unit	Ref.
Power Supply Voltage	Vcc	3.13	3.30	3.47	V	
Power Supply Current	Icc	-	-	1.36	A	Commercial
Case Operating Temperature	Tc	0	-	+70	°C	Commercial
Bit Rate Each Lane	Br			28	Gbps	
9/125um G.652 SMF	Lmax	-	-	10	km	

Electrical Characteristics (TOP=25°C, Vcc=3.3Volts)

Parameter	Symbol	Min	Typ	Max	Unit	Ref.
Transmitter						
Input differential impedance	Rin	85	100	115	Ω	1
Differential data input swing	Vin, pp	150	-	1200	mV	
TX Disable-High	-	Vcc-0.8	-	Vcc	V	
TX Disable-Low	-	Vee	-	Vee+0.8	V	
TX Fault-High	-	Vcc-0.8	-	Vcc	V	
TX Fault-Low	-	0	-	0.8	V	
Receiver						
Output differential impedance	Rin	85	100	115	Ω	1
Single ended data output swing	Vout, pp	200	-	1100	mV	2
LOS-High	-	Vcc-0.8		Vcc	V	
LOS-Low	-	0		0.8	V	



Notes:

1. AC coupled.
2. Into 100 ohm differential termination.


Optical Characteristics (TOP=25°C, Vcc=3.3 Volts)

Parameter	Symbol	Min	Typ	Max	Unit	Ref.
Transmitter						
Optical Wavelength	L0	1294.53	1295.56	1296.59	nm	
	L1	1299.02	1300.05	1301.09	nm	
	L2	1303.54	1304.58	1305.63	nm	
	L3	1308.09	1309.14	1310.19	nm	
Side-mode Suppression Ratio	SMSR	30			dB	
Total Average Launch Power	PT			10.5	dBm	
Average Launch Power @25.78Gb/s, each Lane		-4.3		+4.5	dBm	
Optical Modulation Amplitude @25.78 Gb/s, each Lane	OMA	-1.3		+4.5	dBm	
Average Launch Power @27.95Gb/s, each Lane		-0.6		+4.0	dBm	
Extinction Ratio	ER	4			dB	
Receiver						
RX Sensitivity @25.78Gb/s, each lane	SENS	-	-	-10.6	dBm	1,2
RX Sensitivity(OMA) @25.78 Gb/s, each lane	SENS	-	-	-8.6	dBm	2
RX Sensitivity @27.95Gb/s, each lane	SENS	-	-	-8	dBm	
Receiver Overload @25.78Gb/s		4.5	-	-	dBm	
Receiver Overload @27.95Gb/s		2.9	-	-	dBm	
Difference in Receive Power between any two Lanes (OMA) @25.78Gb/s				7.5	dB	
Difference in Receive Power between any two Lanes (OMA) @27.95Gb/s				6	dB	
LOS De-Assert	LOSD	-	-	-12	dBm	
LOS Assert	LOSA	-25	-	-	dBm	
LOS Hysteresis	-	0.5	-	-	dB	

Notes:

1. The Max is reference value.
2. Measured with PRBS 2³¹-1 at 1E-12 BER.

■ Mechanical Specifications




APQP2LRB3CDL10

■ EEPROM Information

EEPROM memory map specific data field description is as below:



APQP2LRB3CDL10





■ **Digital Diagnostic Monitoring Interface**

Four transceiver parameter values are monitored. The following table defines the Monitory parameter's accuracy.

Parameter	Range	Accuracy	Calibration
Temperature	0 to +70°C	±3°C	Internal
Voltage	2.97 to 3.63V	±3%	Internal
Bias Current	0 to 100mA	±10%	Internal
RX Power	-11 to 4.5dBm	±3dB	Internal

■ **Revision History**

Revision	Initiated	Reviewed	Approved	DCN	Release Date
V1.0	Chuck.chen	Sun.bin	Ding.zheng	New Released.	Jun 29, 2017
V2.0	Colin Huang	Billy Tang	Ding Zheng	Add OMA SEN	Nov 5, 2018

■ **For More Information**

ATOP Corporation

Tel: +86-755-86674946

Fax: +86-755-86296723

Email: sales@atoptechnology.com

Web: www.atoptechnology.com